

STITCHES & GAUGE


Limestone SGT301

Construction	Multi Level Loop
Tile Size	500 x 1000mm
Yarn Type	FITTON Premium Nylon
Stain/ Soil Resistant	Resistec
Dye Method	100% Solution Dyed
Tufted Face Weight	627gm/m ² (18.5oz/yd ²) [±5%]
Gauge	1/10
Stitches per inch	11.7
Tufts	117
Finished Pile Height	4.13mm (0.16") [±5%]
Finished Pile Thickness	2.79mm (0.11") [±5%]
Average Density	6055oz/yd ³
Secondary Backing	Sus-Pac Thermoplastic
Total Thickness Total	7.2mm (0.284") [±5%]
Weight	3,017gm/m ² (88.97oz/yd ²) [±5%]


Performance Specifications

Tuft Bind	ASTM D1335 > 8lbs
Hexapod Test	ASTM D5252 > 3.0 at 12,000 cycles
Flammability (Radiant Panel Test)	ASTM E648 ≥ 0.45 (Class I)
Smoke Density	ASTM E662 ≤ 450
Soiling	ASTM D6540
Stain Resistance	AATCC 175
Dimensional Stability	ASTM D7570 < 0.2%
Methenamine Pill Test	ASTM D2859 (Self-Extinguishing)
Colorfastness to Light	(AATCC 16E) ≥ 4.0 at 80 Hours
Colorfastness to Crocking	(AATCC 165) ≥ 4.0 Wet or Dry
Electrostatic Propensity	(AATCC 134) 20% R.H., 70° F. ≤ 3.5 KV
Texture Appearance Retention Rating	(TARR) Commercial End-Use Applications
Indoor Air Quality	CRI Green Label Plus™


Recommended Installation Method




Monolithic




Ashlar




Brick



Stagger



Herringbone



Basket weave

